

NAME

`gvmap.sh` – pipeline for running gvmap

SYNOPSIS

gvmap.sh [-vV?] [options] [-o outfile] [files]

DESCRIPTION

gvmap.sh takes as input a graph in DOT format, performs a layout, runs the output through gvmap and renders the output. At some point, it is hoped to integrate all of these tasks into gvmap.

OPTIONS

The following options are supported:

- a k** The integer k specifies the average number of artificial points added along the bounding box of the labels. Such artificial points are added to avoid a country boundary cutting through the boundary box of the labels. Computing time is proportional to k; hence, for large graphs, a small value of k is suggested. If k = -1, a suitable value of k is automatically selected based on the graph size. By default k = -1.
- K layout** specifies which program should be used for the initial layout. By default, sfdp is run. Also by default, the layout is passed the flag `-Goverlap=prism`. This can be overridden using a `-g` flag.
- T format** specifies the final output format. This works the same way as the `-T` flag for any Graphviz layout program.
- N attr=val** specifies the setting of a default node attribute during the rendering phase. This works the same way as the `-N` flag for any Graphviz layout program.
- G attr=val** specifies the setting of a graph attribute during the rendering phase. This works the same way as the `-G` flag for any Graphviz layout program.
- E attr=val** specifies the setting of a default edge attribute during the rendering phase. This works the same way as the `-E` flag for any Graphviz layout program.
- n attr=val** specifies the setting of a default node attribute during the layout phase. This works the same way as the `-N` flag for any Graphviz layout program.
- g attr=val** specifies the setting of a graph attribute during the layout phase. This works the same way as the `-G` flag for any Graphviz layout program.
- e attr=val** specifies the setting of a default edge attribute during the layout phase. This works the same way as the `-E` flag for any Graphviz layout program.
- A flag** specifies a flag to be passed to gvmap. For example, `gvmap.sh -Ae -As3` causes gvmap `-e -s3` to be run.
- v** Set verbose mode.
- V** Print version information and exit.
- ?** Print usage information and exit.

EXAMPLES

The following invocation creates a map with edges in semi-transparent light gray and nodes laid out using sfdp:

```
gvmap.sh -Ae -Ecolor=#55555522 -Tpng foo.gv > foo.png
```

It is equivalent to running the pipeline

```
sfdp -Goverlap=prism foo.gv | gvmap -e | neato -n2 -Ecolor=#55555522 -Tpng > foo.png
```

AUTHOR

Emden R. Gansner <erg@research.att.com>

SEE ALSO

gvmap(1), sfdp(1), neato(1), gvpr(1)

E. R. Gansner, Y. Hu, S. G. Kobourov, "GMap: Visualizing graphs and clusters as maps," Proc. Pacific Vis. 2010, pp. 201-208.